

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)


PCT

(10) International Publication Number
WO 2005/052978 A3

- (51) International Patent Classification⁷: **G21K 5/00**, (72) Inventors; and
B01J 19/08 (75) Inventors/Applicants (for US only): **AIZAWA, Koichi**
[JP/JP]; c/o Matsushita Electric Works, Ltd., 1048,
(21) International Application Number: **PCT/JP2004/017969**
Oaza-Kadoma, Kadoma-shi, Osaka 571-8686 (JP). **ICHI-**
(22) International Filing Date: **25 November 2004 (25.11.2004)**
HARA, Tsutomu [JP/JP]; c/o Matsushita Electric Works,
(25) Filing Language: **English** Ltd., 1048, Oaza-Kadoma, Kadoma-shi, Osaka 571-8686
(JP). **KOMODA, Takuya** [JP/JP]; c/o Matsushita Electric
(26) Publication Language: **English** Works, Ltd., 1048, Oaza-Kadoma, Kadoma-shi, Osaka
571-8686 (JP). **IKEDA, Jyunji** [JP/JP]; c/o Matsushita
Electric Works, Ltd., 1048, Oaza-Kadoma, Kadoma-shi,
Osaka 571-8686 (JP). **BABA, Toru** [JP/JP]; c/o Matsushita
Electric Works, Ltd., 1048, Oaza-Kadoma, Kadoma-shi,
Osaka 571-8686 (JP).
- (30) Priority Data:
2003-394655 25 November 2003 (25.11.2003) JP
2003-394653 25 November 2003 (25.11.2003) JP
2004-128856 23 April 2004 (23.04.2004) JP
2004-128824 23 April 2004 (23.04.2004) JP
- (74) Agents: **NISHIKAWA, Yoshikiyo** et al.; Hokuto Patent
Attorneys Office, Umeda-Daiichiseimei Bldg. 5th Floor,
12-17, Umeda 1-chome, Kita-ku, Osaka-shi, Osaka 530-
0001 (JP).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR MODIFYING OBJECT WITH ELECTRONS GENERATED FROM COLD CATHODE ELECTRON EMITTER



(57) Abstract: Apparatus and method for modifying an object with electrons are provided, by which the object can be uniformly and efficiently modified with the electrons under a pressure substantially equal to atmospheric pressure even when having a relatively wide surface area to be treated. This method uses a cold-cathode electron emitter having the capability of emitting electrons from a planar electron emitting portion according to tunnel effect, and preferably comprising a pair of electrodes, and a strong field drift layer including nanocrystalline silicon disposed between the electrodes. The object is exposed to electrons emitted from the planar electron emitting portion by applying a voltage between the electrodes. It is preferred that an energy of the emitted electrons is selected from a range of 1 eV to 50 keV, and preferably 1 eV to 100 eV.



GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

- (88) **Date of publication of the international search report:**

24 November 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.